clicktronic

DISPLAYPORT CABLE

Brilliant images in 8K or 4K and smooth gameplay thanks to G-Sync[™] and FreeSync[™] over 0.5 to 5 metres and many years. The reason: a strong plug, gold-plated connectors and a flexible triple shielded premium cable.



A PLUG THAT PROTECTS AGAINST CABLE BREAKAGE

The plug of the Clicktronic DisplayPort cable consists of three ABS and PVC parts, making it both flexible and robust: if you, for instance, pull the cable with a jerk, it absorbs some of the energy and protects the inner conductor.

GOLD-PLATED CONNECTORS TO ENSURE A LONG SERVICE LIFER

To make sure that the connectors remain rust-free, they are coated with 24 carat gold. This prevents them from oxidising. Plus: Unlike many materials, gold is excellent at transmitting signals – for resistance-free transmission, completely without any interruptions.

TRIPLE SHIELDED TO AVOID FLICKERING

No flickering, even if several cables run in parallel or the smartphone is lying right next to the cable: the triple shielding consisting of aluminium foil and copper braiding intercepts interfering signals. Even with stronger electromagnetic fields.

OFC INNER CONDUCTORS FOR BRILLIANT SIGNAL QUALITY

Pin-sharp images, brilliant audio – even after years: the inner conductors made from 99.9% oxygen-free copper (OFC) are designed not to come into contact with oxygen. This means that they do not oxidise and they transmit signals excellently, just like on the very first day.

clicktronic

A FLEXIBLE AND ROBUST PVC JACKET

The robust PVC jacket protects the Clicktronic DisplayPort cable and keeps it flexible enough to bend around any corner – no matter how long it has spent in one position. The reason: the PVC does not absorb water, even in humid conditions. This means that the cable does not become porous.

SUBJECT TO CHANGE. MODEL SIMILAR. ALL BRAND NAMES ARE REGISTERED TRADEMARKS OF THEIR RESPECTIVE OWNERS.

clicktronic



DISPLAYPORT CABLE

HIGH RESOLUTION OVER 0.5 TO 5 METRES

Smooth streaming, presenting and gameplay: The Clicktronic DisplayPort cable allows you to transmit signals from a computer to a screen – over 0.5 to 5 metres and with a resolution of up to 8K (7680 × 4320 px) at 60 Hz or 4K (3840 × 2160 px) at 120 Hz.

G-SYNC[™] AND FREESYNC[™] FOR SMOOTH IMAGES

Perfect for games where quick reactions are crucial: the cable supports G-SyncTM and FreesyncTM. This allows the graphics card to adapt to the monitor's refresh rate (VRR). The images always appear at exactly the right moment.



SECURE HOLD, OPTIMAL SIGNAL

The plug locks automatically. This means it sits securely in the socket, the connection between all of the contacts is maintained perfectly and the transmission functions optimally – even when used with movable monitors. To disconnect the cable, simply press the unlocking mechanism on the plug.





ALL ADVANTAGES AT A GLANCE

HIGH RESOLUTION From up to 8K (7680 × 4320 px) at 60 Hz or 4K (3840 x 2160 px) at 120 Hz with up to 32.4 Gbit / s.

SMOOTH GAMEPLAY G-Sync™ and FreeSync™ compatible.

SECURE HOLD Thanks to the mechanical locking with an unlocking mechanism. BRILLIANT SIGNAL QUALITY

No oxidation thanks to an inner conductor made from 99.9% oxygen-free copper (OFC).

NO FLICKERING Thanks to triple insulation consisting of aluminium foil and copper braiding.

FLEXIBLE AND ROBUST CABLE Thanks to the PVC jacket, which can be bent optimally even after years. STRONG PLUG

PVC and ABS ensure maximum flexibility in the event of a jerk on the cable.

RUST-FREE CONNECTOR Even after years – thanks to a 24 carat gold coating.

SUBJECT TO CHANGE. MODEL SIMILAR. ALL BRAND NAMES ARE REGISTERED TRADEMARKS OF THEIR RESPECTIVE OWNERS.

clicktronic



DISPLAYPORT CABLE

SIGNAL TRANSMISSION

TRANSMISSION TYPES: digital audio and video signals MAX. TRANSMISSION RATE (Gbit / s): 32.4 (0.5 – 5 m) WAVE IMPEDANCE (Ω): 100

CABLE CROSS-SECTION

PVC jacket Earth Insulation Copper braiding ... AL- / Mylar®- shielding

. OFC conductor

.....Insulation

AL-/Mylar®-

shielding

SUPPORTED FORMATS

AUDIO STANDARDS	Dolby Digital / Plus, Dolby True HD, DTS-HD Master Audio™, DVD-Audio, SA-CD
OTHER STANDARDS	3D, HDCP, DRM, E-DDC, E-EDID, 4K (2160 i / p), Full HD (1080 i / p), HD ready (720 i / p), SDTV (480 i / p) (1 – 7,5 m); 3D, HDCP, DRM, E-DDC, E-EDID, Full HD (1080 i / p), HD ready (720 i / p), SDTV (480 i / p) (10 m)
COLOUR SPACES	16 / 24 bit RGB / YUV, Deep Color, x.v.Color™

CIRCUIT DIAGRAM



PRODUCT DATA

CABLE LENGTH	\varnothing inner conductor	AWG	Ø OUTER JACKET
1-5 m	1×0.32 mm	28	7.3 mm

CABLE LENGTH	RRP	Packaged unit	SKU	EAN
1.0 m	19.99€	1/20/40	40992	4040849409929
2.0 m	24.99 €	1/15/30	40994	4040849409943
3.0 m	29.99 €	1/12/24	40995	4040849409950
5.0 m	39.99 €	1/10/20	40996	4040849409967



SUBJECT TO CHANGE. MODEL SIMILAR. ALL BRAND NAMES ARE REGISTERED TRADEMARKS OF THEIR RESPECTIVE OWNERS.

