

1	2	3	4	5	6	7	8	9	10	11	12	13	14		
A	Anschlussdiagramm / Wiring diagram CN1 CN2 A1 A12 B1 B12 A2 A3 A4 A9 B4 B9 A5 A6 A7 A8 A10 A11 B2 B3 B5 B6 B7 B8 B10 B11 SHELL A1 A12 B1 B12 A2 A3 A4 A9 B4 B9 A5 A6 A7 A8 A10 A11 B2 B3 B5 B6 B7 B8 B10 B11 SHELL <td colspan="10"> CN1 B12 8.25± 0.03 B1 A1 2.40± 0.03 A12 14.3 CN2 A1 6.65± 0.20 A12 B12 2.56± 0.04 B1 8.34^{+0.08}_{-0.02} 6.5 13.0 19.0 </td> <td>A</td>				CN1 B12 8.25± 0.03 B1 A1 2.40± 0.03 A12 14.3 CN2 A1 6.65± 0.20 A12 B12 2.56± 0.04 B1 8.34^{+0.08}_{-0.02} 6.5 13.0 19.0										A
B															B
C															C
D															D
E															E
F					Adapter USB-C™ auf USB-C™ 90° - erlaubt einen nach oben oder unten abgewinkelten Anschluss - führt das USB-C™-Kabel eng am Gerät entlang, um ein Abknicken und Kabelbruch effektiv zu vermeiden - Ermöglicht mit USB 3.2 SuperSpeed-Datentransferraten von bis zu 10 Gbit/s - zum Übertragen von Daten, Musik, Fotos und HD-Filmen - Kompatibel mit Windows und Android sowie dem Apple MacBook mit USB-C™-Port/Thunderbolt™ 4, abwärtskompatibel zu USB 2.0 und 1.1 - Dank Plug & Play ist die Installation zusätzlicher Treiber nicht erforderlich <td colspan="5"> USB-C™ to USB-C™ Adapter 90° - allows for an upward or downward angled connection - runs the USB-C™ cable closely along the device, effectively preventing kinking and cable breakage - Provides SuperSpeed data transfer rates of up to 10 Gbit/s thanks to USB 3.2 - for transferring data, music, photos and HD films - Compatible with Windows and Android as well as the Apple MacBook with USB-C™ port/Thunderbolt™ 4, downward compatible with USB 2.0 and 1.1 - Thanks to Plug & Play, no additional drivers are required <td>F</td></td>					USB-C™ to USB-C™ Adapter 90° - allows for an upward or downward angled connection - runs the USB-C™ cable closely along the device, effectively preventing kinking and cable breakage - Provides SuperSpeed data transfer rates of up to 10 Gbit/s thanks to USB 3.2 - for transferring data, music, photos and HD films - Compatible with Windows and Android as well as the Apple MacBook with USB-C™ port/Thunderbolt™ 4, downward compatible with USB 2.0 and 1.1 - Thanks to Plug & Play, no additional drivers are required <td>F</td>					F
G					Anschluss, Typ: USB-C™-Buchse Anschluss 2, Typ: USB-C™-Stecker Standard: USB 3.2 Gen 2x2 (USB 3.2) max. Übertragungsrate: 10 Gbit/s Farbe: schwarz Abmessungen (L x B x H): 20 x 10 x 10 mm Gewicht: 10 g					Connection, type: USB-C™ female Connection 2, type: USB-C™ male Standard: USB 3.2 Gen 2x2 (USB 3.2) max. transmission rate: 10 Gbit/s Color: black Dimensions (L x W x H): 20 x 10 x 10 mm Weight: 10 g					G
H															H
I	Änderungen Datum Name 01.03.2024 ir 21.02.2025 fw 28.02.2025 fw				Datum Name gez.: 24.01.2024 ir gepr.: 24.01.2024 ZK Norm:		Bezeichnung USB-C ADAP C-M/C-F 90° 3.2 schwarz Zeichnungs-Nr.: 55556		Blatt 1 von 1		I				
J					Änderungen vorbehalten / Subject to change										J
1	2	3	4	5	6	7	8	9	10	11	12	13	14		